



BANDIT ZT1844 STUMPGRINDER



PRODUCTIVITY

DUAL DRIVE MOTORS



The rubber track undercarriage is friendly to delicate lawns but sturdy enough to track through rough terrain.

38HP KOHLER ENGINE



The powerful 38HP petrol motor features electronic fuel injection so it is easy to start, even in very cold conditions.

MORE PRODUCTIVE



The Bandit ZT1844 has a 44" swing arc so it is extremely productive for such a compact machine. It has a taller grinding height and deeper grinding depth than machines of a comparable size, so it can cover more area in a shorter time.

HIGH QUALITY CONTROLS



The ZT1844 is fitted with user friendly operator controls that are connected by heavy duty valves for years of dependable service. Controls swivel to give the operator greater manoeuvrability and better vision of the stump.

OPERATOR SAFETY



The red safety bar above the cutter wheel keeps the operator away from the spinning wheel during grinding.

EASY TO SERVICE



All major service points are easily accessible. With fewer moving parts there is less maintenance and less down time.

BANDIT ZT1844 SPECIFICATIONS

GENERAL

SELF PROPELLED	2WD standard
WEIGHT645 kg
LENGTH96" (243cm)
WIDTH29" (73cm)
HEIGHT.....	.46" (116cm)

CUTTING DIMENSIONS

CUTTING HEIGHT.....	.22" (56cm)
CUTTING DEPTH12" (30cm)
CUT/SWING WIDTH.....	.44" (1.1m)

ENGINE

ENGINE BRAND.....	Kohler Command Pro
STANDARD ENGINE POWER	38hp (28kw)
MAX TORQUE	60.7 ft. lb
FUEL TANK CAPACITY	27 litres
FUEL TYPE.....	Unleaded

BETTER CUTTER WHEEL DESIGN

The grinders 18" diameter cutter wheel features Green teeth, a tooth & pocket system that allows the operator to rotate the tooth with a standard wrench to provide a fresh cutting edge.

PRODUCTIVITY

The grinder has a wider swing arc that covers more area. It has a taller grinding height and a deeper grinding depth for getting to the roots of large stumps.

SELF PROPELLED DRIVE SYSTEM

The ZT1844 is driven by a 300cc hydraulic motor with a chain/sprocket drive. The ZT1844 will travel approximately 140fpm reducing the time required to get to the stump.

ELECTRICAL SYSTEM

SYSTEM VOLTAGE	12v
BATTERY	CCA 340
GAUGES.....	Fuel & Hourmeter
SWITCHES.....	Cutter speed
SHUTDOWN SYSTEM	Emergency shutdown

HYDRAULIC SYSTEM

HYDRAULIC TANK CAPACITY	27 litres
RECOMMENDED OIL TYPE.....	Agrifarm Utto

GROUND DRIVE

TRAVEL SPEED	0 – 2.7 kph (0-140FPM)
VARIABLE	Control switch to vary speed

CUTTER WHEEL

CUTTER WHEEL DRIVE SYSTEM	Belt Driven
CUTTER WHEEL DIAMETER	18" (50.8cm)
CUTTER WHEEL WIDTH	1" (25.4mm)
TOOTH TYPE.....	Green Teeth
NUMBER OF TEETH.....	8

RUBBER TRACK

The rubber track carriage was designed for rough terrain yet does not damage lawns.

EASY TO SERVICE

All major service points are easily accessible. With fewer moving parts there is less maintenance and less downtime.

