



PORTAFILL 5000CT



The Portafill 5000CT is designed with heavy duty screening applications in mind. Small enough to fit inside a container for transport but strong enough to withstand the toughest of materials. High performance and excellent reliability are key features of this machine.

Feeder/Hopper

Feed Length 3760mm (12'4")
Feed Height 3005mm (9'10")

Feeder/Hopper

1000mm (40") Wide Belt
Variable Speed
Hopper Volume 4 cubic meters (5.2 cu yards)

Engine

Deutz D2011 L04i
(EU Stage IIIA,
EPA Tier 3)
Deutz TD2.9L4
(EU Stage IIIB,
EPA Tier 4i)

Screen Box

Bolted 2 Bearing Screen
3200mm (10'6") x 1200mm (4')

Wing Conveyors

750mm (30") Wide
Discharge Height 2880mm (9'5")

Oversize Conveyor

1000mm (40") Wide
Discharge Height
2638mm (8'8")

Features

- Highly aggressive screen action for excellent performance in difficult materials.
- Folding wing conveyors for transport
- 2in1 oversize product conveyor for optionally mixing oversize and midsize product
- Low fuel consumption for low cost of ownership

Transport		Working	
Width	2.2m (7'5")	Width	11.4m (37'6")
Length	10.6m (34'10")	Length	10.6m (35'1")
Height	2.5m (8'5")	Height	3m (9'10")
Weight			
		14,000kgs	
		30,800lbs	

Portafill International Ltd, Dungannon Business Park,
Killyliss Road, Dungannon, Co Tyrone, BT70 1RP
T: 44 (0)28 8772 3505 | reception@portafill.com | www.portafill.com

All dimensions and weights are approximate. Subject to change without notice.

PORTAFILL 5000CT